

REFRESH YOUR HOME'S WATER

Life in the city can be convenient, but it also comes with some downfalls when it comes to your water. Municipal water sources need to add chlorine to protect the water from bacteria as it travels through the system to your house. Once you are ready to use the water, this layer of protection is no longer need and can cause strong odors or affect the taste if left untreated.

High levels of chlorine can also dry out sensitive skin while bathing. The chemical strips away your body's natural oils, leaving skin and hair brittle and itchy.

With the Hague Hydroclean HC3 Activated Carbon Filter, you can enjoy fresh, odor-free water from every faucet. Our automated, self-sufficient filter is designed to efficiently reduce chlorine as water passes through the tank. This low maintenance filtration system requires no on going replacement costs like other carbon filters available today. Bringing you a worry-free way to water for you and your family to enjoy.













SYSTEM FEATURES

WATER YOU WILL LOVE TO USE

- 1 ENHANCED TECHNOLOGY: Patented valve design includes built-in bypass to the filter when it's unnecessary, like watering the lawn.
- DIGITAL CONTROLLER: Provides an easy to read screen to make setting adjustments, see current flow rate, and hold your programming during a loss of power.
- 3 HIGH-PERFORMANCE MEDIA: Activated Carbon captures the chlorine to prevent it from traveling into your home for the life of the product, eliminating the need for costly filter replacements.
- 4 GRAVEL BEDDING: Provides consistent and efficient water flow throughout the tank.







SPECIFICATIONS

Product Number	HC3 1CF
Iron in solution	0 ppm
Minimum pH-standard units	7
Media Type	Activated Carbon
Media Tank Size-Dia. x Ht.	10" x 47" (25 x 119 cm)
Media amount	1.33 cu. ft. (0.04 cu. m)
Flow Rate @ 15 psi drop	8 gpm (30 mL/m)
Pipe Size	1" (2.54 cm)
Product Dimensions	11" x 51" (28cm x 130 cm)
Quartz Gravel	14 lb (6.4 kg)
Water Pressure-min-max	30–120 psi (2.1–8.3 bar)
Water temperature-min-max	33–120 °F (0.56–48.9 °C)
Minimum water volume for backwash	5.0 gpm (19 L/min)

Additional HC3 models available: HC3 1NF Acid Neutralizer, HC3 25, 35, 48, 64, 105 Water Softeners.



4343 S. Hamilton Road | Groveport, OH 43125 614-836-2115 | Fax: 614-836-5349