



ENJOY LIFE WITH SOFT WATER

Maximize your money, time, and space with the most advanced, compact water treatment system offered by Hague Quality Water International.

The Maximizer® Model 97 offers a minimal footprint while providing maximum water quality. Featuring a smart touch controller, single cabinet design, and an easy to fill brine tank, this Maximizer® is a convenient way to improve your every day life. Feel the difference when you get the soft, high-quality water you deserve.




Environmentally Friendly
Leaves Minimal Footprint



Ultra-Fil
Whole-House Filtration



Softer Skin and Hair
Retains Moisture Better



Fabrics Stay Bold
Soaps Wash Away Easier

Model 97
MAXIMIZER®

ADVANCED DESIGN

- ① **SMART TOUCH CONTROLLER:** Easy-to-use touch screen interface for quick setting adjustments and viewing current flow rates.
- ② **PATENTED VALVE:** Equipped with a built-in bypass valve and test port for easy use.
- ③ **SUPERIOR WATER DISTRIBUTION:** This custom engineered baffle distributes the incoming water gently through the tank to maximize efficiency and quality.
- ④ **ULTRA-FIL:** Self cleaning dirt and sediment filter that replaces the need to change filters or cartridges. Models available to treat sulfur or chlorine issues.
- ⑤ **FINE MESH RESIN:** Vacuum packed fine mesh resin equals less salt, time, and water usage versus standard mesh resin.
- ⑥ **SAFETY SHUT-OFF:** The safety shut-off system is a backup feature that can protect your investment in case of a system failure.



MAXIMIZER® MODEL 97

Max Compensated Hardness	90 gpg (1540g/L)
Max Ferrous Iron Reduction	10 ppm
Filtration-Nominal Rating	20 Microns
Media Amount	Chlorostat (Model 97MMBI) Sulfurstat (Model 97MMPI) Fine Mesh Cation Resin - 1 cu. ft. (28 L)
Salt Used/Capacity: #1 Setting	1 lb/5,400 grains (0.5 kg/350 grams)
#2 Setting	3 lb/13,700 grains (1.4 kg/888 grams)
#3 Setting	6 lb/23,700 grains (2.7 kg/1540 grams)
#4 Setting	9 lb/30,800 grains (4.1 kg/2000 grams)
Minimum pH	7
Peak Flow Rate @ 15 psi drop	10.7 gpm (40.5 L/min)
Plumbing Connections	1¼" Male (MNPT)
Salt Storage Capacity	170 lbs (77 kg)
Electrical Requirements	115 V, 60 Hz
Min./Max. Water Temperature	40-120° F (4-49° C)
Water Pressure (min., max.)	20-120 psi
Dimensions	15"W x 30"H x 19"D



4343 S. Hamilton Road | Groveport, OH 43125
614-836-2115 | Fax: 614-836-5349